Removable Guardrails and Barricading

Many defects on guard rails and barricades are routinely observed that have led to dropped objects, in particular where movable modular types are used.



 $\overline{\mathbf{V}}$

 $\sqrt{}$

 $\sqrt{}$

 $\sqrt{}$


 $\sqrt{}$

Prior to starting any task around guard rails; particularly lifting and stacking, check that all fastenings and pins are in place and secured.

Ensure modular rails can be inserted into pockets and secured with a through-pin and safety keeper pin (do not use incompatible materials as this may cause corrosion).



If there is a likelihood that movable sections of guardrail may be snagged during lifting, consider temporarily removing and securing these away from the task.




Barricade systems should be of suitable




 $\sqrt{}$

Ensure guard rails are functionally designed for the area. Not all guard rails are capable of withstanding additional forces or loading.






All guard rail and barricade securing should be visually inspected on a regular basis to ensure integrity of fastenings.





Report any defects in guard rails and barricades (e.g. cracks, deformation, collision damage, corrosion; particularly around pockets or fastenings).

Ensure all temporary barricading such as netting or hoarding is secured against the environment, inspected regularly and removed when the work is complete.





Ensure any modifications to guard rails carefully consider all design requirements, impact / snagging / fatigue potential and address appropriate secondary retention and safety securing requirements.



CHOOSE YOUR FUTURE MAKE A DIFFERENCE

For further details of DROPS Guidance, Resources, Membership or Training:

Email: admin@dropsonline.org www.dropsonline.org